



FEARLESS PERFORMANCE®

**116.530**

Assembly Gloves with Cut Protection

Crinkled latex coating, Typhoon® HPPE liner.



- 15-gauge Typhoon® HPPE liner provides great cut protection (level E) perfect for handling glass, metals, and plastics.
- Crinkled latex coating enhances dry and wet grip.
- Breathable liner gives exceptional comfortability and dexterity (Level 5).
- OEKO-TEX® 100 Approved.

Standards and Approvals

EN ISO
21420:2020EN
388:2016+A1:2
018

2X42E

ANSI/ISEA
105-2016

CUT

Suitable for:

Window manufacturing | Handling and repairing glass and windows | Bottling | Handling of metal sheets | Handling of heavy equipment.



Breathable



Cut Resistant



Precision

CATEGORY:

Cut Resistant Gloves

INDUSTRY:

Automotive

Building and Construction

Glass

Logistics and Warehousing

Maintenance

Oil, Gas and Mining

Pulp and Paper

Steel and Metal

STANDARDS AND APPROVALS:

EN ISO 21420:2020

EN 388:2016+A1:2018

OEKO-TEX® Standard 100

ANSI/ISEA 105-2016

CE Cat.II

PROTECTION AND RESISTANCE:

Cut Resistant

Tear Resistant

FEATURES AND PROPERTIES:

Breathable

Precision

Seamless



PRODUCT DETAILS

Liner material :	Typhoon®
Coating material :	Latex
Grip :	Dry, Wet
Glove fit :	Tight fit
Size :	6 7 8 9 10 11 12

Length :	21-27 cm
Color :	Blue, Grey

PACKING / TRANSPORT

Sales Units Per Bundle: 12
Sales Units Per Outer Case: 144